

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

30. (Currently Amended) An attachment assembly comprising a plurality of attachments releasably attached to a common spine and intended to be secured to an article by a tagging gun, the each attachment comprising:

a limp flexible cord formed from several fibre strands which have been twisted together, the cord being without resilient tendency to return to an initial position;

a cross-shaped member or a T-shaped member, said cross-shaped or T-shaped member having a plastic cross bar and down bar, the down bar having a first section extending from the cross bar and a second section comprising an enlarged flange, the enlarged flange being moulded around one end of the flexible cord; and

a terminal member moulded at the other end of the flexible cord, wherein, at one end of the flexible cord, the flexible cord is fixed to the down bar of the cross-shaped or T-shaped member, said terminal member being fixed to the other end of the flexible cord.

wherein each of said attachments is releasably attached to said common spine by an extension bar extending from the common spine to said cross bar so that each attachment is independently severable from said common spine, and wherein the diameter of the cord is greater than that of the first section of the down bar, but smaller than that of the enlarged flange.

31-32. (Canceled)

33. (Currently Amended) An ~~attachment~~assembly according to claim 30 wherein the cord is formed of a natural material.

34. (Currently Amended) An ~~attachment~~assembly according to claim 33 wherein the cord is formed of cotton.

35-36. (Canceled)

37. (Currently Amended) An assembly according to claim ~~35-30~~ further comprising teeth on the common spine, between the attachments.

38. (Currently Amended) Apparatus for making an assembly comprising a plurality of attachments releasably attached to a common spine, each attachment comprising:

a limp flexible cord formed from several fibre strands which have been twisted together, the cord being without resilient tendency to return to an initial position;

a cross-shaped member or a T-shaped member, said cross-shaped or T-shaped member having a plastic cross bar and down bar, the down bar having an enlarged flange, the enlarged flange being moulded around one end of the flexible cord; and

a terminal member moulded at the other end of the flexible cord, ~~wherein, at one end of the flexible cord, the flexible cord is fixed to the cross-shaped or T-shaped member, said terminal member being fixed to the other end of the flexible cord, said assembly further comprising a common spine, wherein~~ each of said attachments being

is releasably attached to said common spine via by an extension bar extending from the common spine to said cross-shaped member or said T-shaped membercross bar, each attachment being independently severable from said common spine, said apparatus comprising a mould having:

a first recess for moulding said common spine and said cross-shaped or T-shaped members;

second recesses for moulding said terminal members; and

cord support means for supporting a cord that extends between and at least partially into said first and second recesses, wherein said first recess includes enlarged flange portions for surrounding the cord.

39. (Canceled)

40. (Currently Amended) A method for making an assembly comprising a plurality of attachments releasably attached to a common spine, each attachment comprising:

a limp flexible cord formed from several fibre strands which have been twisted together, the cord being without resilient tendency to return to an initial position;

a cross-shaped member or a T-shaped member, said cross-shaped or T-shaped member having a plastic cross bar and down bar, the down bar having an enlarged flange, the enlarged flange being moulded around one end of the flexible cord; and

a terminal member moulded at the other end of the flexible cord, wherein, ~~at one end of the flexible cord, the flexible cord is fixed to the cross-shaped or T-shaped member, said terminal member being fixed to the other end of the flexible cord, said~~

~~assembly further comprising a common spine, wherein each of said attachments being~~  
~~is releasably attached to said common spine via said cross-shaped member or said T-~~  
~~shaped member~~by an extension bar extending from the common spine to said cross  
bar, each attachment being independently severable from said common spine,  
said method including the steps:

- a) providing a mould with a first recess for moulding said common spine and  
said cross-shaped or T-shaped members and second recesses for moulding said  
terminal members;
- b) placing said flexible cords in the mould so that they extend between and pass  
at least partially into said recesses;
- c) injecting liquid plastics material into said recesses and allowing it to solidify.

41. (Previously Presented) A method according to claim 40 wherein in step (b)  
a separate flexible cord is placed between each respective second recess and said first  
recess.

42. (Previously Presented) A method according to claim 40 further including the  
step of cutting said cord to separate the attachments formed in step (c) from surplus  
cord that is not part of said attachments.

43. (Previously Presented) A method according to claim 40 wherein following  
step (c), the attachments that have been formed in step (c) are pulled through the  
mould so that lengths of cord fixed to the terminal members of said attachments, but

not forming part of the attachments, extend between said first and second recesses, and then step (c) is repeated to form further attachments.

44. (Previously Presented) A method according to claim 43 wherein the mould is opened to allow the cords to be pulled through the mould and then the mould is closed to clamp the cords in place.

45. (Previously Presented) A method according to claim 40 wherein in step (b) the flexible cord is positioned so that it extends back and forth between said second recesses and the first recess.

46. (Previously Presented) A method according to claim 45 wherein, after step (c), the cord is cut to sever cord connections between adjacent terminal portions and the cord is cut to sever cord connections between adjacent cross-shaped or T-shaped members.